

High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.3

Revision Date 11/27/2024

Print Date 11/27/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : Microlite® MW XG, Microlite® WHXG, Range-Glas® XG, SPIN-GLAS® TC XG, SPIN-GLAS® WH XG

Manufacturer or supplier's details

Company : Johns Manville
Address : P.O. Box 5108
Denver, CO USA 80217-5108

Telephone : +1-303-978-2000
Emergency telephone number : 24-Hour Number: +1-800-424-9300 (CHEMTREC)

Company : Johns Manville Canada Inc.
Address : 5301 42 Avenue
Innisfail, AB Canada T4G 1A2
Telephone : +1-303-978-2000
Emergency telephone number : 24-Hour Number: +1-800-424-9300 (CHEMTREC)

Recommended use of the chemical and restrictions on use

Recommended use : thermal and/or acoustic insulation
Restrictions on use : For professional users only.
Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Hazardous Products Regulations

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Glass fiber product

Hazardous components

Non-hazardous according to the OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Hazardous Products Regulations, when used as intended.

Relevant ingredients

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|--------------|-----------------------|
| non-biopersistent (biosoluble) glass fibers | Not Assigned | >= 80 - <= 100 % |

High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.3

Revision Date 11/27/2024

Print Date 11/27/2024

SECTION 4. FIRST AID MEASURES

| | | |
|---|---|---|
| General advice | : | Handle in accordance with good industrial hygiene and safety practice. |
| If inhaled | : | Remove person to fresh air. If signs/symptoms continue, get medical attention. |
| In case of skin contact | : | In case of contact, flush skin with plenty of water for at least 5 minutes while removing contaminated clothing and shoes. If skin irritation persists, call a physician. Wash contaminated clothing before re-use. |
| In case of eye contact | : | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If easy to do, remove contact lens, if worn. Protect unharmed eye. If eye irritation persists, consult a specialist. |
| If swallowed | : | Rinse mouth with water to remove dust or fibers and drink plenty of water to help reduce irritation. If symptoms persist, call a physician. |
| Most important symptoms and effects, both acute and delayed | : | Temporary mechanical abrasion (itching) of skin, eyes and respiratory tract may occur upon exposure to fibers or dust during handling of this product and cannot occur unless there is direct contact. Abrasion effects should subside after cessation of exposure. |
| Protection of first-aiders | : | If potential for exposure exists refer to Section 8 for specific personal protective equipment. |
| Notes to physician | : | Treat symptomatically. |

SECTION 5. FIREFIGHTING MEASURES

| | | |
|---|---|--|
| Suitable extinguishing media | : | Carbon dioxide (CO ₂) Foam Dry powder Water |
| Unsuitable extinguishing media | : | none |
| Specific hazards during firefighting | : | Under the influence of high temperatures, e.g. during a fire in the warehouse, decomposition products like carbon oxide may be released due to the low content of organic compounds. |
| Hazardous combustion products | : | carbon oxides nitrogen oxides Acrylic monomers Hydrocarbons |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| | | |
|--|---|-----------------------|
| Personal precautions, protective equipment and | : | Avoid dust formation. |
|--|---|-----------------------|

High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.3

Revision Date 11/27/2024

Print Date 11/27/2024

emergency procedures

Environmental precautions : Should not be released into the environment.

Methods and materials for containment and cleaning up : Clean up promptly by scoop or vacuum.
Pick up and arrange disposal without creating dust.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : No special protective measures against fire required.

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
Minimize dust generation and accumulation.
Do not breathe vapours/dust.
Do not get in eyes or mouth or on skin.
For personal protection see section 8.

Conditions for safe storage : Keep in a dry place.

Materials to avoid : No materials to be especially mentioned.

Further information on storage stability : Stable at normal ambient temperature and pressure.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|---|--------------|-------------------------------------|--|-----------|
| synthetic vitreous fibers, glass wool fibers | Not Assigned | TWA | 1 fibers/cm ³ | ACGIH |
| Fibrous glass dust | Not Assigned | TWA | 3 fibers/cm ³ | NIOSH REL |
| | | TWA (total) | 5 mg/m ³ | NIOSH REL |
| Inert or Nuisance Dust, Particulates Not Otherwise Regulated (PNOR) | Not Assigned | PEL (Total dust) | 15 mg/m ³ | OSHA |
| | | PEL (Respirable particulate matter) | 5 mg/m ³ | OSHA |

As a member of the North American Insulation Manufacturers Association (NAIMA), Johns Manville subscribes to the NAIMA Product Stewardship Program (NPSP). Under the NPSP, Johns Manville recommends that exposures be limited to the NAIMA-OSHA voluntary Permissible Exposure Limit (vPEL) of 1 f/cc TWA. The NPSP also includes work practice and respiratory protection recommendations for exposures over the vPEL. For more information, see NAIMA's Health and Safety Reference Library (website: <http://insulationinstitute.org/tools-resources/resource-library/health-safety/>) to find the Product Stewardship Program Pocket Folder (N052) and other Fact Sheets.

Engineering measures : During initial heat-up to operating temperatures above 220 °C (428 °F), thermal decomposition of the organic binder/sizing

High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.3

Revision Date 11/27/2024

Print Date 11/27/2024

may occur.

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines.

If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process.

Personal protective equipment

- | | | |
|-----------------------------|---|--|
| Respiratory protection | : | No personal respiratory protective equipment normally required. During initial heat-up to operating temperatures above 220 °C (428 °F), thermal decomposition of the organic binder/sizing may occur. Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. |
| Hand protection Material | : | Protective gloves |
| Remarks | : | For prolonged or repeated contact use protective gloves. |
| Eye protection | : | Safety glasses with side-shields |
| Skin and body protection | : | Wear protective clothing, such as long-sleeved shirts and pants. Change working clothes after each workshift. Remove and wash contaminated clothing before re-use. |
| Hygiene measures | : | Handle in accordance with good industrial hygiene and safety practice. |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- | | | |
|---|---|-------------------|
| Appearance | : | roll |
| Colour | : | No data available |
| Odour | : | slight |
| Odour Threshold | : | No data available |
| pH | : | Not applicable |
| Melting point/freezing point | : | Not applicable |
| Initial boiling point and boiling range | : | Not applicable |
| Flash point | : | Not applicable |
| Evaporation rate | : | Not applicable |
| Flammability (solid, gas) | : | No data available |
| Upper explosion limit | : | Not applicable |
| Lower explosion limit | : | Not applicable |

High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.3

Revision Date 11/27/2024

Print Date 11/27/2024

| | |
|--|---------------------|
| Vapour pressure | : Not applicable |
| Relative vapour density | : Not applicable |
| Relative density | : No data available |
| Density | : Not applicable |
| Solubility(ies) | |
| Water solubility | : insoluble |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Auto-ignition temperature | : No data available |
| Thermal decomposition | : Not applicable |
| Viscosity | |
| Viscosity, dynamic | : Not applicable |
| Viscosity, kinematic | : Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : None known. |
| Conditions to avoid | : Exposure to moisture |
| Incompatible materials | : hydrofluoric acid |
| Hazardous decomposition products | : Thermal decomposition can lead to release of irritating gases and vapors. |

SECTION 11. TOXICOLOGICAL INFORMATION

| | |
|-------------|---|
| IARC | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. |
| OSHA | No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA (29 CFR 1910 Subpart Z, Toxic and Hazardous Substances). |
| NTP | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |

Further information

Product:

Remarks: During initial heat-up to operating temperatures above 220 °C (428 °F), thermal decomposition of the organic binder/sizing may occur. Use local exhaust ventilation, or other

High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.3

Revision Date 11/27/2024

Print Date 11/27/2024

engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process.

Remarks: Temporary mechanical abrasion (itching) of skin, eyes and respiratory tract may occur upon exposure to fibers or dust during handling of this product and cannot occur unless there is direct contact. Abrasion effects should subside after cessation of exposure.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : Due to the properties of the product, a hazard to the environment may not be expected.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

Land transport

USDOT: Not classified as a dangerous good under transport regulations

TDG: Not classified as a dangerous good under transport regulations

Sea transport

IMDG: Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO: Not classified as a dangerous good under transport regulations

High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.3

Revision Date 11/27/2024

Print Date 11/27/2024

SECTION 15. REGULATORY INFORMATION

TSCA list

TSCA - 5(a) Significant New Use Rule List of Chemicals : Not relevant

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : Not relevant

SARA 311/312 Hazards : No SARA Hazards**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop. 65

This product does not require a warning under the California Safe Drinking Water and Toxic Enforcement Act (Proposition 65).

The components of this product are reported in the following inventories:

: These products are considered articles under both U.S. and international products and as such, these products do not require registration or notification on the various country-specific inventories.

SECTION 16. OTHER INFORMATION

Further information

Revision Date : 11/27/2024

Full text of other abbreviationsACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits
OSHA : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA : 8-hour time-weighted average
NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA / PEL : Permissible exposure limit

High-Temperature Fiberglass Appliance and Transportation OEM Insulation

Version 3.3

Revision Date 11/27/2024

Print Date 11/27/2024

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.